

ClimaWrap

Breathable Membrane



| WIDTH | LENGTH | AREA |
|--------|--------|--------------------|
| 1370mm | 30m | 41.1m ² |

| THIS PRODUCT MEETS THE REQUIREMENTS OF AS/NZS 4200.1 | | |
|--|---|------------------|
| PRODUCT IDENTIFIER | CLIMAWRAP BREATHABLE MEMBRANE | |
| DUTY | LIGHT WALL (for the use in walls and gables only) | |
| VAPOUR CLASSIFICATION | CLASS 4 | VAPOUR PERMEABLE |
| VAPOUR PERMEABILITY | 3.9670 µg/N·s | |
| WATER CONTROL CLASSIFICATION | WATER BARRIER | |
| FLAMABILITY INDEX | LOW (≤ 5) | |
| ELECTRICAL CONDUCTIVITY | NON-CONDUCTIVE | |

| EMITTANCE | | |
|-----------|-------------------|----------|
| VALUE | CLASSIFICATION | CATEGORY |
| 0.58 | IR NON-REFLECTIVE | NN |
| 0.56 | IR NON-REFLECTIVE | |

Classifications in accordance with AS/NZS 4200.1. This product should be installed in accordance with AS/NZS 4200.2.

Storage: ClimaWrap must be kept dry and out of contact with alkaline products, cement and mortar.

Installation Recommendations:

ClimaWrap shall be installed in accordance with AS/NZS 4200.2 Pliable Building Membranes and Underlays, Part 2 Installation Requirements. ClimaWrap shall be installed horizontally as a continuous membrane by fixing to all framing members with the printed side facing out, from the top plate to the bottom plate on concrete slabs or bearers in timber constructions. Joins must be overlapped by 150mm to maintain weather tightness. To achieve an air barrier, all joins, cuts and penetrations shall be taped using seaming tape.

Ensure to repair any damage or tears to ClimaWrap to maintain the integrity of the membrane.

Breathable and Airtight Air Barrier Membrane

- ✓ Class 4 Vapour Permeable
- ✓ Water and Air Barrier
- ✓ Low Flamability; Suitable for BALs In Bushfire-Prone Areas

Light duty breathable membrane for the use in:

- Light weight clad walls
- Brick veneer walls





ClimaWrap

Breathable Membrane



| WIDTH | LENGTH | AREA |
|--------|--------|------------------|
| 1500mm | 30m | 45m ² |

| THIS PRODUCT MEETS THE REQUIREMENTS OF AS/NZS 4200.1 | | |
|--|---|------------------|
| PRODUCT IDENTIFIER | CLIMAWRAP BREATHABLE MEMBRANE | |
| DUTY | LIGHT WALL (for the use in walls and gables only) | |
| VAPOUR CLASSIFICATION | CLASS 4 | VAPOUR PERMEABLE |
| VAPOUR PERMEABILITY | 3.9670 µg/N·s | |
| WATER CONTROL CLASSIFICATION | WATER BARRIER | |
| FLAMABILITY INDEX | LOW (≤ 5) | |
| ELECTRICAL CONDUCTIVITY | NON-CONDUCTIVE | |

| EMITTANCE | | |
|-----------|-------------------|----------|
| VALUE | CLASSIFICATION | CATEGORY |
| 0.58 | IR NON-REFLECTIVE | NN |
| 0.56 | IR NON-REFLECTIVE | |

Classifications in accordance with AS/NZS 4200.1. This product should be installed in accordance with AS/NZS 4200.2.

Storage: ClimaWrap must be kept dry and out of contact with alkaline products, cement and mortar.

Installation Recommendations:

ClimaWrap shall be installed in accordance with AS/NZS 4200.2 Pliable Building Membranes and Underlays, Part 2 Installation Requirements. ClimaWrap shall be installed horizontally as a continuous membrane by fixing to all framing members with the printed side facing out, from the top plate to the bottom plate on concrete slabs or bearers in timber constructions. Joins must be overlapped by 150mm to maintain weather tightness. To achieve an air barrier, all joins, cuts and penetrations shall be taped using seaming tape.

Ensure to repair any damage or tears to ClimaWrap to maintain the integrity of the membrane.

Breathable and Airtight Air Barrier Membrane

- ✓ Class 4 Vapour Permeable
- ✓ Water and Air Barrier
- ✓ Low Flamability; Suitable for BALs In Bushfire-Prone Areas

Light duty breathable membrane for the use in:

- Light weight clad walls
- Brick veneer walls

