

Lunar

Mineral Fiber Acoustic Ceiling

 RH99



Features:

- Wet-formed mineral fiber
- Good sound absorption.
- Easy to install. Non-directional patterns.
- Superior Sag Resistance
- High Durability
- Color: White

Usage Areas:

- Schools/Institutions/Libraries/
Reading Rooms
- Offices/Conference/Meeting rooms
- Corridors/Lobbies
- Book Stores/Retail/Shopping Malls
- Light Industries/Canteens



Acoustic Aesthetic Durable

 **ROCK**
Ceilings for Professionals

Edge Type	Panel Size (Nominal)	Item Number	Fire Class	NRC	CAC	LR	Voc Emissions	Recycled Content	Tee Grid Designs	
SE (Square Edge) 	600x600x16	LS 01M	Class A1/Class 1 ²	0.55	35	0.84	LOW	45%	A,B	
	2' x 2' x 5/8"	LS 02		0.55	35	0.84			A,B	
	600x1200x16	LS 03M		0.55	35	0.84			A	
	2' x 4' x 5/8"	LS 04		0.55	35	0.84			A	
TE (Tegular Edge) 	600x600x16	LT 01M	Class A1/Class 1 ²	0.55	35	0.84	LOW	45%	C,D	
TBE (Tegular with Bevel Edge) 	600x600x16	LB 01M	Class A1/Class 1 ²	0.55	35	0.84	LOW	45%	E,F,G,H	

*Other sizes and special items available upon request.

Standards:

NRC:

ASTM C423-09a

CAC:

ASTM E1414-06 and
ASTM E413-04

LR:

ASTM E1477-98a
(values are shown as averages)

Fire Class:

1. ASTM E84
2. AS/NZS 3837

Performances:

RH99:

Resist sagging at relative humidity of 99% and temperature 104 °F or 40 °C.
Does not include standing water and outdoor applications.

Mold/Mildew Resistance:

Contains a broad spectrum antimicrobial additive on the face and back of the panel that resist the growth of mold and mildew.

Thermal Insulation:

R-1.5

Maintenance:

Can be cleaned easily with a soft brush or vacuum.

Distributed by:



Acoustic Aesthetic Durable

ROCK SG PTE LTD

10 Anson Road, International Plaza, #05-17, Singapore 079903 • Email: info@rock-sg.sg



Ceilings for Professionals